

This range of wall mounted units are discreet and modern, the perfect match for any type of decor. Optimum efficiency and comfort, thanks to features like 2-area intelligent eye.

## FTXLS-K + RXLS-M

Guaranteed heating operation down to -25°C



Efficiency data		FTXLS + RXLS		25K + 25M		35K + 35M			
Cooling capacity	Min./Nom./Max.	kW		1.6/2.5/4.4		1.7/3.5/5.0			
Heating capacity	Min./Nom./Max.	kW		1.0/4.7/6.6/3.90 (1)		1.0/5.4/7.2/4.50 (1)			
Power input	Cooling	Min./Nom./Max.	kW		0.32/0.67/2.33		0.32/0.95/2.33		
	Heating	Min./Nom./Max.	kW		0.24/1.10/2.36		0.24/1.31/2.88		
Seasonal efficiency (according to EN14825)	Cooling	Energy label		A++					
		Pdesign	kW	2.50		3.50			
		SEER		6.62		6.91			
		Annual energy consumption	kWh	132		177			
	Heating (Average climate)	Energy label		A++					
		Pdesign	kW	3.20		3.80			
		SCOP		4.62		4.60			
		Annual energy consumption	kWh	947		1,147			
<b>Indoor unit</b>		<b>FTXLS</b>	<b>25K</b>	<b>35K</b>					
Casing	Colour	White							
Dimensions	Unit	HeightxWidthxDepth	mm					298x900x215	
Weight	Unit	kg					12		
Air filter	Type	Removable / washable / mildew proof							
Sound power level	Cooling	dBA					59		
	Heating	dBA					62		
Sound pressure level	Cooling	High/Nom./Low/Silent operation	dBA					45/39/33/21	
	Heating	High/Nom./Low/Silent operation	dBA					47/39/33/19	
<b>Outdoor unit</b>		<b>RXLS</b>	<b>25M</b>	<b>35M</b>					
Dimensions	Unit	HeightxWidthxDepth	mm					550x858x330	
Weight	Unit	kg					40		
Sound power level	Cooling	dBA					61		
	Heating	dBA					61		
Sound pressure level	Cooling	High/Low	dBA					48/44	
	Heating	High/Low	dBA					49/45	
Operation range	Cooling	Ambient	Min.~Max.	°CDB				-10~46	
	Heating	Ambient	Min.~Max.	°CWB				-25~18	
Refrigerant	Type/Charge/GWP	kg					R-410A/1.3/1,975		

(Note) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load (1) Maximum heating capacity at -15°C outdoor temperature