

Wall mounted unit

FTXTA-CW + RXTA-C



BLUEEVOLUTION nepura stylish



Fireplace logic



Coanda effect - heating



Heat boost



Guaranteed operation down to -30°C



Onecta app

Where innovation meets creativity, even at ambient temperatures down to -30°C

- › Guaranteed heating capacity down to -30°C
- › Even temperature distribution thanks to fireplace logic
- › Compact design in matt crystal white
- › Perfect temperature distribution thanks to Coanda effect
- › Intelligent thermal sensor: air flow is adjusted when detecting temperature differences
- › Onecta app
- › Voice control
- › Bluevolution range: lower environmental impact
- › Seasonal efficiency values up to A+++ in cooling and heating
- › Daikin Flash Streamer technology: powerful air purification
- › Practically inaudible
- › Heat boost: fast heating during start-up (pair only)

FTXTA-CW + RXTA-C



Indoor unit		FTXTA		30CW
Dimensions	Unit	HeightxWidthxDepth		mm
				295 x798 x189
Weight	Unit			kg
				12
Air filter	Type			Removable / washable
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/High	m ³ /min
				4.9 / 6.0 / 9.0 / 13.1
		Heating	Silent operation / Low / Medium / High	m ³ /min
				5.0 / 5.8 / 8.2 / 12.3
Sound power level	Cooling			dBA
				60.0
	Heating			dBA
				60.0
Sound pressure level	Cooling	Silent operation/Low/High		dBA
				20.0 / 25.0 / 43.0
	Heating	Silent operation/Low/High		dBA
				19.0 / 24.0 / 41.0
Control systems	Infrared remote control		ARC466A84	
	Wired remote control		BRC073A4	


Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m | See separate drawing for electrical data

Outdoor unit		RXTA		30C
Dimensions	Unit	HeightxWidthxDepth		mm
				605 x930 x376
Weight	Unit			kg
				42
Sound power level	Cooling			dBA
				60
	Heating			dBA
				60
Sound pressure level	Cooling	Nom.		dBA
				48.0
	Heating	Nom.		dBA
				49.0
Operation range	Cooling	Ambient	Min.-Max.	°CDB
				-10 ~46
	Heating	Ambient	Min.-Max.	°CWB
				-31 ~18
Refrigerant	Type			R-32
	GWP			675.0
	Charge			kg/TCO ₂ Eq
				0.97 / 0.66
Piping connections	Liquid	OD		mm
				6.35
	Gas	OD		mm
				9.50
	Piping length	OU - IU	Max.	m
				20
	Additional refrigerant charge			kg/m
				0.02 (for piping length exceeding 10m)
	Level difference IU - OU	Max.		m
				15.0
Power supply	Phase/Frequency/Voltage		Hz/V	
			1~/50 /220-240	
Current - 50Hz	Maximum fuse amps (MFA)		A	
			16	

Contains fluorinated greenhouse gases | See separate drawing for operation range | See separate drawing for electrical data

Efficiency data		FTXTA + RXTA		30CW + 30C
Cooling capacity	Min./Nom./Max.			kW
				1.2 / 3.0 / 4.6
Heating capacity	Min./Nom./Max.			kW
				0.8 / 3.2 / 7.10
Power input	Cooling	Nom.		kW
				0.62
	Heating	Nom.		kW
				0.64
Space cooling	Energy efficiency class		A+++	
	Capacity	Pdesign	kW	
			3.00	
	SEER			8.75
	Annual energy consumption	kWh/a		
				120
Space heating (Average climate)	Energy efficiency class		A+++	
	Capacity	Pdesign	kW	
			3.00	
	SCOP/A			5.17
	Annual energy consumption	kWh/a		
				812
Space heating (Cold climate)	Energy efficiency class		A+	
	Capacity	Pdesignh	kW	
			4.38	
	SCOP/C			4.09
	Annual energy consumption	kWh/a		
				2,248
Nominal efficiency	EER			4.89
	COP			5.01
	Annual energy consumption	kWh		
				310
	Energy labeling Directive	Cooling/Heating		
				A/A
Current - 50Hz	Maximum fuse amps (MFA)		A	
			16	

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)



ECPN23-062

08/2023



Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: www.eurovent-certification.com

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

